

MA613

03- Step Rolling Ladders, Platform Height 28"

Reg. 375.00\$

PRODUCT DESCRIPTION

3-step rolling ladders

ITEM#MA613

No. of Steps: 3

Platform Height: 28"

Platform Depth: 16"

Step Width: 22"

Frame Material: Steel

Step Type: Perforated

Certification(s): CSA certified to the ANSI standard a14.7

Base Depth: 30"

Base Width: 24"

Top Step Depth: 16"

Top Step Width: 22"

Step Size: 22" W x 8" D

Weight: 42 lbs.

Top Step Size: 22" W x 16" D

Capacity: 300 lbs.

Colour: Blue



Ideal wherever there is a need to reach bulky materials
Rolls easily into position and locks firmly to the floor for
maximum safety

2 to 6 step ladders operate on spring-loaded casters

Casters retract under operator's weight, rubber feet drop
down

For more information contact us by phone at 450 642-1118 or by email at info@laflammeindustriels.com.

First step on all 8 to 16 step ladders activates the floor locking mechanism (step off and kick release to make the ladder mobile)

Non-clogging slip-resistant steel steps

Frame is rugged welded 1" round steel tubing

8 to 16 step ladders shipped knocked down, easily assembled

Capacity: 300 lbs.

Durable Kleton blue enamel finish

CSA certified to the ANSI standard A14.7 ; Note: Ladders are not to be used as work platforms.

Categories: [2 - 3 steps](#), [Ladder on wheels](#)

PRODUCT DESCRIPTION

3-step rolling ladders

ITEM#MA613

No. of Steps: 3

Platform Height: 28"

Platform Depth: 16"

Step Width: 22"

Frame Material: Steel

Step Type: Perforated

Certification(s): CSA certified to the ANSI standard a14.7

Base Depth: 30"

Base Width: 24"

Top Step Depth: 16"

Top Step Width: 22"

Step Size: 22" W x 8" D

Weight: 42 lbs.

For more information contact us by phone at 450 642-1118 or by email at info@laflammeindustriels.com.

Top Step Size: 22" W x 16" D

Capacity: 300 lbs.

Colour: Blue

Ideal wherever there is a need to reach bulky materials

Rolls easily into position and locks firmly to the floor for maximum safety

2 to 6 step ladders operate on spring-loaded casters

Casters retract under operator's weight, rubber feet drop down

First step on all 8 to 16 step ladders activates the floor locking mechanism (step off and kick release to make the ladder mobile)

Non-clogging slip-resistant steel steps

Frame is rugged welded 1" round steel tubing

8 to 16 step ladders shipped knocked down, easily assembled

Capacity: 300 lbs.

Durable Kleton blue enamel finish

CSA certified to the ANSI standard A14.7 ; Note: Ladders are not to be used as work platforms.