

## SGU467

### 60 gal.- Flammable Storage Cabinet

Reg. 2,300.00\$

#### PRODUCT DESCRIPTION

Door Type: Self-Closing

Capacity: 60 gal.

Width: 34"

Depth: 34"

Height: 65"

No. Of Doors: 2

No. Of Shelves: 2

Standard(s) Met: FM/NFPA/OSHA

Warranty: 10 Year Limited



- Safety cabinet door self-closes and is equipped with a fusible link that melts when the ambient temperature reaches 165°F (74°C)
- Double-wall 18-gauge welded steel construction with 1-1/2" air space
- Dual 2" capped vents with flame arrestors
- Full-height piano hinges open a full 180° for easy access
- Recessed handle
- 2" high leak-proof door sill
- All shelves are adjustable on 2-1/2" centers
- Adjustable leveling feet
- Tough corrosive-resistant finish
- Meets NFPA Code 30 and OSHA standard 1910 106 for storage for class I, II and III liquids

Category: [Flammable Storage Cabinet](#)

For more information contact us by phone at 450 642-1118 or by email at [info@laflammeindustriels.com](mailto:info@laflammeindustriels.com).

## PRODUCT DESCRIPTION

Door Type: Self-Closing

Capacity: 60 gal.

Width: 34"

Depth: 34"

Height: 65"

No. Of Doors: 2

No. Of Shelves: 2

Standard(s) Met: FM/NFPA/OSHA

Warranty: 10 Year Limited

- Safety cabinet door self-closes and is equipped with a fusible link that melts when the ambient temperature reaches 165°F (74°C)
- Double-wall 18-gauge welded steel construction with 1-1/2" air space
- Dual 2" capped vents with flame arrestors
- Full-height piano hinges open a full 180° for easy access
- Recessed handle
- 2" high leak-proof door sill
- All shelves are adjustable on 2-1/2" centers
- Adjustable leveling feet
- Tough corrosive-resistant finish
- Meets NFPA Code 30 and OSHA standard 1910 106 for storage for class I, II and III liquids